

Agency: Commerce, Community and Economic Development**Grants to Municipalities (AS 37.05.315)****Grant Recipient: Kodiak Island Borough****Federal Tax ID: 92-0030845****Project Title:****Project Type: Equipment and Materials**

Kodiak Island Borough - Landfill Leachate Treatment Plant & Related Phase III Improvements

State Funding Requested: \$4,529,000**House District: 35 / R**

One-Time Need

Brief Project Description:

Purchase and installation of a waste water treatment plant

Funding Plan:

Total Project Cost:	\$10,848,000
Funding Already Secured:	(\$6,319,000)
FY2014 State Funding Request:	<u>(\$4,529,000)</u>
Project Deficit:	\$0

Funding Details:

The cost of Phase III is estimated to be \$10,848,000. The funding already secured for Phase III consists of (1) approximately \$500,000 in KIB revenue bonds; and (2) approximately \$5.8 million in Alaska Clean Water Fund loan funds.

Detailed Project Description and Justification:

The Kodiak Island Borough is closing out the existing landfill footprint and creating a new lined cell in accordance with EPA/DEC requirements. The lined cell when in operation will generate leachate that will be treated by an on-site wastewater treatment plant. This structure is a stand-alone skid mounted piece of equipment. It will be installed as Phase III of our landfill expansion project. Phase III is estimated to cost \$10,848,000.

Funding is in place for Phase I and Phase II, with local funds covering about 67% and state funds for the remaining 33%.

An on-site leachate treatment plant was chosen as the method to address leachate produced at the landfill after the alternative of piping it to the City of Kodiak Wastewater Treatment Facility was found not to be a feasible option. This wastewater treatment plant is required to treat wastewater to DEC drinking water standards. The borough also submitted a matching grant application through DEC for the maximum amount allowable for this plant; however, this project currently ranks below the fundable portion of the budget. The borough views this project as a basic infrastructure need for the community.

The purchase and installation of a wastewater treatment plant is the final phase of the Kodiak Landfill Lateral Expansion project. The estimated cost for the purchase, installation and associated equipment of the wastewater treatment plant is \$10,848,000.

The Kodiak Island Borough has secured funding in the amount of \$501,000 in revenue bonds and \$5,818,548 in Alaska

Clean Water Fund loan funds for a total of \$6,319,000. This amount of the local funding is approximately 58% of the estimated cost for this phase. KIB is requesting legislative funding in the amount of \$4,529,000. This funding reduces the borough's need to further request loan funds or issue revenue bonds, both of which obligate the local citizens to higher use fees for repayment of the debt.

If this request is funded, the entire Kodiak Landfill Expansion Project will have be funded with 64% from local funds and 36% from the state once completed.

Project Timeline:

It is anticipated that the process for the purchase of the treatment plant and associated equipment will begin in the summer of 2013 with intallation beginning in late 2013.

Entity Responsible for the Ongoing Operation and Maintenance of this Project:

Kodiak Island Borough

Grant Recipient Contact Information:

Name: Charles E. Cassidy
Title: Manager
Address: 710 Mill Bay Road
Kodiak, Alaska 99615
Phone Number: (907)486-9302
Email: bcassidy@kodiakak.us

Has this project been through a public review process at the local level and is it a community priority? Yes No


Kodiak Island Borough
Kodiak Landfill Lateral Expansion Project
Phase III: Waste Water Treatment Plant

Estimated Cost

Site Work	1,500,000
Building	2,000,000
MBR System	2,650,000
Facility Mechanicals	1,500,000
Design Services	750,000
Eng. Services During Construction	350,000
Chemical Storage	290,000

Other:

DEC Regulatory Requirement	}	\$1,808,000.00
P & Z Conditions of Approval		
Storm Water Drainage		
Plant Start-up Costs		
		<hr/>
		\$10,848,000.00




EQUIPMENT MEZZANINE, CANOPIES AND CEILINGS
1/8"=1'-0"

1 ENLARGED BATHROOM PLAN
1/2" = 1'-0"


FLOOR PLAN
1/8"=1'-0"

NOTE:
SEE O20-A-5001 FOR ACCESSORY
LOCATIONS AND MOUNTING
HEIGHT


KODIAK ISLAND BOROUGH		KODIAK LANDFILL LATERAL EXPANSION PHASE 3 LEACHATE TREATMENT PLANT		KODIAK ISLAND, ALASKA	
CH2MHILL®		LEACHATE TREATMENT PLANT ARCHITECTURAL FLOOR PLAN			
VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING.					
DATE	JANUARY 2013				
PROJ	354650				
DWG	020-A-2000				
SHEET	of				
DRAWN	DR	ME SHARP	REVISION	CHK	APVD
NO.	DATE				
		GH BURLEY		SJ PAYNE	
		C HINDS			




A EAST BUILDING SECTION
 1/8" = 1'-0"
 20-A-2000
 20-A-3001
 20-A-3002




C SHIPS LADDER
 3/8" = 1'-0"
 20-A-2000



D SECTION
 3/8" = 1'-0"
 20-A-2000




B NORTH BUILDING SECTION
 1/8" = 1'-0"
 20-A-2000
 20-A-3001
 20-A-3002




E STAIR SECTION
 1/8" = 1'-0"
 20-A-2000
 20-A-3001
 20-A-3002

KODIAK ISLAND BOROUGH		KODIAK LANDFILL LATERAL EXPANSION PHASE 3 LEACHATE TREATMENT PLANT KODIAK ISLAND, ALASKA	
CH2MHILL®		LEACHATE TREATMENT PLANT ARCHITECTURAL SECTIONS	
NO.	DATE	DR	REVISION
		ME SHARP	GH BURLEY
			SJ PAYNE
			APVD
			BY
			APVD
			C HINDS
VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING.			
DATE	JANUARY 2013		
PROJ	354650		
DWG	020-A-3000		
SHEET	of		

REUSE OF DOCUMENTS: THIS DOCUMENT, AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, AS AN INSTRUMENT OF PROFESSIONAL SERVICE, IS THE PROPERTY OF CH2M HILL AND IS NOT TO BE USED, IN WHOLE OR IN PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CH2M HILL.
 © CH2M HILL 2012. ALL RIGHTS RESERVED.



1 EAST BUILDING ELEVATION
 1/8" = 1'-0"
 X



2 NORTH BUILDING ELEVATION
 1/8" = 1'-0"
 X

KODIAK ISLAND BOROUGH

KODIAK LANDFILL
 LATERAL EXPANSION PHASE 3
 LEACHATE TREATMENT PLANT
 KODIAK ISLAND, ALASKA




CH2MHILL®

LEACHATE TREATMENT PLANT
 ARCHITECTURAL
 NORTH AND EAST ELEVATIONS


VERIFY SCALE	
BAR IS ONE INCH ON ORIGINAL DRAWING.	
DATE	JANUARY 2013
PROJ	354650
DWG	020-A-3001
SHEET	of

NO.	DATE	DR	REVISION	BY
		MF SHARP		
		GH BURLEY	CHK	
			APVD	
				SJ PAYNE
				APVD
				BY
				APVD
				C HINDS

REUSE OF DOCUMENTS: THIS DOCUMENT, AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, AS AN INSTRUMENT OF PROFESSIONAL SERVICE, IS THE PROPERTY OF CH2M HILL AND IS NOT TO BE USED, IN WHOLE OR IN PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CH2M HILL. © CH2M HILL 2012. ALL RIGHTS RESERVED.



1 BUILDING ELEVATION
1/8" = 1'-0"
X



2 BUILDING ELEVATION
1/8" = 1'-0"
X

KODIAK ISLAND BOROUGH

KODIAK LANDFILL
LATERAL EXPANSION PHASE 3
LEACHATE TREATMENT PLANT
KODIAK ISLAND, ALASKA



CH2MHILL®
LEACHATE TREATMENT PLANT
ARCHITECTURAL
SOUTH AND WEST ELEVATIONS

VERIFY SCALE	
BAR IS ONE INCH ON ORIGINAL DRAWING.	
DATE	JANUARY 2013
PROJ	354650
DWG	020-A-3002
SHEET	of

NO.	DATE	DR	REVISION	BY
		MF SHARP		
		GH BURLY	CHK	
		SJ PAYNE	APVD	
		C HINDS	APVD	

REUSE OF DOCUMENTS: THIS DOCUMENT, AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, AS AN INSTRUMENT OF PROFESSIONAL SERVICE, IS THE PROPERTY OF CH2M HILL AND IS NOT TO BE USED, IN WHOLE OR IN PART, FOR ANY OTHER PROJECT WITHOUT THE WRITTEN AUTHORIZATION OF CH2M HILL. © CH2M HILL 2012. ALL RIGHTS RESERVED.

The MBR Treatment System

By David Branham, Wastewater Technician



As promised I will dedicate this article to the membrane bioreactors (MBR) process. A brief description of what it is and how it works is in order, so here goes. The particular illustrations I will be using are from the Zenon brand of membrane technologies. I will also be stating information out of an article printed in the March 2005, issue of WEFTEC.

The MBR system replaces conventional filtration and combines clarification, aeration, and sludge digestion into one simpler and smaller process step. The process incorporates immersing membranes directly in a process tank, thus reducing both capital and operating cost.

The immersed hollow-fiber membrane operates under a slight suction, drawing clean water to the inside of the membrane fiber, while leaving biomass and impurities in the process tank. The suction allows the membrane to be immersed directly inside a new tank or the membranes may be retrofitted into an existing aeration basin, clarifier, or steel tank thus saving the expense of building new process tanks.

Most of the systems mentioned in this article are modular. Individual membrane modules can be combined to form cassettes to meet the required treatment capacity. The advantage is that plant expansion can be in stride with actual community growth, drastically reducing up-front development costs.

- Fits in existing process tanks or clarifiers (ideal for plant expansion)
- Extremely small footprint (1/10th the size of a conventional tertiary plant)
- Resistant to process upsets
- Easy to operate
- Reduces sludge volumes in plants with high SRT
- Produces tertiary quality effluent in a single step
- Modular and easily expandable



Many studies of these types of systems have been performed; the study I will be quoting is from a grant issued by the U.S. Bureau of Reclamation. The project team of *Samer Adham, James DeCarolis, Jude Grounds, Larry Wasserman, and Bill Pearce* had two objectives in mind when they made their study of four different brands of MBRs. Goal One was to obtain operational and water quality data, and Goal Two was to assess MBR performance when treating advanced primary system effluent.


Four different manufactures of MBRs that were included in this study are as follows:

- **Kubota.** The Kubota system consisted of anoxic, pre-nitrification, and nitrification zones. It used 0.4-micron-pore flat-sheet membranes to separate activated sludge and water into solid and liquid. Mixed-liquor suspended solids (MLSS) were recycled from the aerobic tank to the anoxic tank at about four times the permeate rate to enable denitrification. The membranes were relaxed at set intervals to prevent membrane fouling.

There are four process trains, each consisting of an anoxic zone and aerobic zone containing the membranes. Three process trains treat the municipal sewage, while the fourth treats either municipal or industrial wastewater.

Effluent is drawn through the membrane fibers via a low-pressure suction created by permeate pumps, one per process train.

System Summary	
Membrane Type	ZeeWeed® 500
Process Trains	4
Total Membrane Cassettes	40
ZeeWeed® Process Footprint	8,000 ft ²
Overall Plant Footprint	750,000 ft ²




- **Mitsubishi.** The Mitsubishi system included a permeate storage tank and an aerobic tank in which two membrane cassettes of 0.5-micron-pore hollow-fiber membranes were submerged. The membranes were relaxed at set intervals to prevent membrane fouling.
- **USFilter.** The USFilter system included an aerobic tank, a permeate storage tank, and a membrane tank containing four modules of 0.2-micron-pore hollow fiber membranes. During operation, air and MLSS were continuously injected into the membrane tank to scrub and shake the membrane fibers. Permeate water was frequently backwashed from the inside to the outside of the membrane fibers to prevent membrane fouling.
- **Zenon.** The Zenon system included an aerobic tank and membrane tank containing 0.1-micron-pore hollow-fiber membranes. MLSS was recirculated from the aerobic tank to the membrane tank. The membranes were relaxed at set intervals to prevent membrane fouling. At high flux rates, the membranes were also periodically cleaned with chlorine and acid to mitigate fouling.

My conclusion is that these types of treatment systems are the future of the industry. As seen in the above table, all presently proposed TMDL restrictions can be met and/or exceeded with this type of technology. MBR treatment systems are much easier to control and operate, have smaller footprints to build, are resistant to process upsets, have reduction of sludge volumes, and being easily expandable are all big positive pluses for any town or wastewater district. I am looking forward to seeing many of you this summer. David Branham, Wastewater Technician.

The team's studies were quite conclusive and are highlighted in the aforementioned publication. The following table was taken from information supplied by Zenon Environmental, Inc. However, research of test results of the other three systems mentioned above also fell well within these parameters.


Typical Treated Water Results		
	Raw WQ	Treated WQ
BOD (mg/L)	200	< 5
TSS (mg/L)	220	< 2
Turbidity (NTU)	N/A	< 0.2

KODIAK ISLAND BOROUGH KODIAK LANDFILL LATERAL EXPANSION PHASE III: WASTEWATER TREATMENT PLANT



Phase III of the Kodiak Landfill Lateral Expansion Project will construct an onsite waste water treatment facility for treatment of the landfill’s leachate.

The on-site treatment of the leachate stream will be accomplished with an Ultra Filtration facility. The system is designed to collect, contain and direct the raw wastewater stream (leachate) to a collection lagoon where it is pumped to the treatment facility.



The treatment process is based on a Membrane Bioreactor System (MBR) which currently is the best available technology for wastewater treatment facilities. MBR systems offer economic and operational advantages over conventional wastewater treatment facilities as the plants are more compact, have simplified operations and offer a higher quality discharge effluent at comparable lifecycle costs. Upon completion and start up the plant is designed to provide effluent discharge to “drinking water” standards.

Estimated Cost	
Site Work	1,500,000
Building	2,000,000
MBR System	2,650,000
Facility Mechanicals	1,500,000
Design Services	750,000
Eng. Services During Construction	350,000
Chemical Storage	290,000
Other: DEC Regulatory Requirement, P & Z Conditions of Approval, Storm Water Drainage, Plant Start-up Costs	1,808,000
	Total \$10,848,000
Funding	
KIB Revenue Bonds	501,000
Alaska Clean Water Fund Loan	5,818,000
	Sub-Total \$6,319,000
Legislative Request	4,529,000
	Total \$10,848,000



Kodiak Island Borough

Phase III – Landfill

Waste Water Treatment Plant

Contact: Woody Koning, Director

Engineering & Facilities Department

Phone (907) 486-9340

E-mail: wkoning@kodiakak.us

About the Waste Water Treatment Plant...

- Treats leachate generated from the Kodiak Island Borough Landfill.
- Treatment of the landfill's leachate is required by ADEC and EPA to meet drinking water standards.
- A properly operating landfill is an essential piece of community infrastructure for residential, commercial and industrial use.
- Construction of the Waste Water Treatment Plant is the **final phase** of the Kodiak Island Landfill Lateral Expansion project.
- A State contribution of \$4,529,000 will reduce landfill user rates which have already been increased by the project.
- Kodiak Island Borough's local contribution to the total project will remain significant at 64 % if the legislative request is funded.